


# 120-M-311/-411

Pin strip

Plug-in direction parallel to PCB, with support



## GENERAL INFORMATION

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Pitch                  | 5 mm                                                                                                                |
| No. of poles           | 2 - 12                                                                                                              |
| Usable with            | all plug connectors of series 120                                                                                   |
| Additional Information | Ordering information<br>...M-311: with support and without side walls<br>...M-411: with support and with side walls |

## TECHNICAL DATA

|                          |                          |       |       |
|--------------------------|--------------------------|-------|-------|
| Overvoltage Category     | III                      | III   | II    |
| Pollution Severity Level | 3                        | 2     | 2     |
| Rated Voltage            | 250 V                    | 320 V | 630 V |
| Rated Impulse Voltage    | 4 kV                     | 4 kV  | 4 kV  |
| Rated Insulation Voltage | 250 V acc. to EN 60998-1 |       |       |
| Rated Current            | 12 A                     |       |       |
| Hole in PCB              | ø 1,4 mm                 |       |       |

## APPROVALS

|                                                                                     | Current [A] | Voltage [V] | Group | AWG | [Nm] |
|-------------------------------------------------------------------------------------|-------------|-------------|-------|-----|------|
|  | 15          | 300         | B     |     |      |
|                                                                                     | 10          | 300         | D     |     |      |
|  | 15          | 300         | B     |     |      |
|                                                                                     | 10          | 300         | D, E  |     |      |
|  |             |             |       |     |      |

## MATERIAL

|                            |                                |
|----------------------------|--------------------------------|
| Moulding                   | PA, grey, V-0                  |
| Comparative Tracking Index | CTI ≥ 600                      |
| Insulating Group           | I                              |
| Temperature Range          | -40°C up to 100°C              |
| Solder pin                 | 1,0 x 1,0 mm; tin plated brass |

## OPTIONS / ACCESSORIES

- Consecutive numbering
- Special marking according to drawing
- Self-adhesive marking strip BST-5,00
- Pitch of 10 mm for larger clearance and creepage distances
- Other solder pin lengths on request
- Coding elements 120-K
- Connectors equipped with coding elements on request
- Pin strips with fastening flanges, see 120-M-217
- Pin strips with connecting flanges, see 120-M-215

## CONFIGURATIONS

| Poles | Part number  | Article number | Part number  | Article number | Length (L) | Packaging | PU  |
|-------|--------------|----------------|--------------|----------------|------------|-----------|-----|
| 2     | 120-M-311/02 | 10.806.402     | 120-M-411/02 | 10.806.426     | 10,00 mm   | Box       | 200 |
| 3     | 120-M-311/03 | 10.806.403     | 120-M-411/03 | 10.806.427     | 15,00 mm   | Box       | 200 |
| 4     | 120-M-311/04 | 10.806.404     | 120-M-411/04 | 10.806.428     | 20,00 mm   | Box       | 100 |
| 5     | 120-M-311/05 | 10.806.405     | 120-M-411/05 | 10.806.429     | 25,00 mm   | Box       | 100 |
| 6     | 120-M-311/06 | 10.806.406     | 120-M-411/06 | 10.806.430     | 30,00 mm   | Box       | 100 |

further number of poles on request

