


# 181-A-121

PCB connector

Screw connection, wire entrance vertical to PCB





## GENERAL INFORMATION

Pitch	5,08 mm
No. of poles	1 - 12
Areas of application	Particularly suitable for confined mounting space or only single-sided access.

## TECHNICAL DATA

Clamping Range	<i>solid / stranded / AWG</i>		
	0,14 - 4 mm <sup>2</sup> / 0,14 - 2,5 mm <sup>2</sup> / 26 - 12 AWG		
Rated Cross Section	2,5 mm <sup>2</sup>		
Wire Stripping Length	9 mm ± 0,5 mm		
Overvoltage Category	III	III	II
Pollution Severity Level	3	2	2
Rated Voltage	320 V	320 V	630 V
Rated Impulse Voltage	4 kV	4 kV	4 kV
Rated Insulation Voltage	450 V acc. to EN 60998-1		
Rated Current	24 A		
Hole in PCB	ø 1,4 mm		
Torque	0,4 Nm		

## APPROVALS

	Current [A]	Voltage [V]	Group	AWG	[Nm]
	20	300	B	24 - 12	0,4
	10	300	D	24 - 12	0,4
	20	300	B	24 - 12	0,4
	10	300	D, E	24 - 12	0,4

## MATERIAL

Moulding	PA, grey, V-0
Comparative Tracking Index	CTI ≥ 600
Temperature Range	-40°C up to 100°C
Pressure clamp	Tin plated copper
Screw	M2,5; zinc plated steel, blue passivated
Solder pin	1,0 x 0,8 mm; tin plated copper
Terminal body	Zinc plated steel, blue passivated
Pressure plate	Brass, bright

## OPTIONS / ACCESSORIES

- Consecutive numbering
- Special marking according to drawing
- Self-adhesive marking strip BST-5,08
- Connected to larger number of poles

## CONFIGURATIONS

Poles	Part number	Article number	Length (L)	Packaging	PU
1	181-A-121/01	11.819.051	7,58 mm	Box	500
2	181-A-121/02	12.819.051	12,66 mm	Box	250
3	181-A-121/03	13.819.051	17,74 mm	Box	250
4	181-A-121/04	14.819.051	22,82 mm	Box	100
5	181-A-121/05	15.819.051	27,90 mm	Box	50
6	181-A-121/06	16.819.051	32,98 mm	Box	50

further number of poles on request

